

AMENDMENTS TO THE CLAIMS

1. (Previously Presented) A method comprising:
identifying a power state of a first system, the power state to be one of at least a first and second power states, the second power state to consume less power than the first power state; and
in response to the system being in the second power state, switching, without using a main operating system, a serial Advanced Technology Attachment (SATA) link from the first system to a link with an autonomous subsystem.
2. (Currently Amended) The method ~~according to~~ claim 1, wherein the power state ~~is power state~~comprises of an Advanced Configuration Power Interface Specification (ACPI-S) state.
3. (Canceled)
4. (Canceled)
5. (Currently Amended) The method ~~according to~~ claim 2, wherein~~[[:]]~~ if the ACPI state is S0, S1, or S2 then the SATA is switched to the first system,~~[[;]]~~ and if the ACPI state is S3, S4, or S5 then the SATA is switched to the subsystem.

6. (Currently Amended) The method ~~according to~~ claim 2, wherein ~~[[:]]~~ if the ACPI state is S0, or S1 then the SATA is switched to the first system~~[[:]]~~ and if the ACPI state is S2, S3, S4, or S5 then the SATA is switched to the subsystem.
7. (Currently Amended) A machine-readable medium having stored thereon data representing sets of instructions~~[[,]]~~ which~~1~~, when executed by a ~~processor~~machine, ~~causes said processor to cause the machine to perform the following:~~
- identify a power state of a first system, the power state to be at least one of a first and second power states, the second power state to consume less power than the first power state; and
- in response to the system being in the second power state, switch, without use of a main operating system, a serial Advanced Technology Attachment (SATA) link from the first system to a link with an autonomous subsystem.
8. (Canceled)
9. (Currently Amended) A system comprising:
- a memory;
- a serial Advanced Technology Attachment (SATA) device connected to the
- memory and to a switch; and
- a the switch to
- connect the system to the SATA device when the system is in a first power state, and ~~the switch to~~

connect an autonomous subsystem to the SATA device, without using use
of a main operating system, when the system is in a second power
state, the second power state to consume less power than the first
power state.

10. (Currently Amended) The system of claim 9, wherein the switch connecting the SATA device alternately connects ~~does not connect both~~ the system and the subsystem to the SATA devices ~~simultaneously~~.
11. (Previously Presented) The system of claim 9, wherein the switch operation is controlled by signals from the system.
- 12-15. (Cancelled)
16. (New) The machine-readable medium of claim 7, wherein the power state comprises an Advanced Configuration Power Interface Specification (ACPI) state.
17. (New) The machine-readable medium of claim 16, wherein if the ACPI state is S0, S1, or S2 then the SATA is switched to the first system, and if the ACPI state is S3, S4, or S5 then the SATA is switched to the subsystem.
18. (New) The machine-readable medium of claim 16, wherein if the ACPI state is S0, or S1 then the SATA is switched to the first system, and if the ACPI state is S2, S3, S4, or S5 then the SATA is switched to the subsystem.

19. (New) An apparatus comprising:
a serial Advanced Technology Attachment (SATA) device connected to a switch;
and
the switch to
connect the system to the SATA device when the system is in a first power
state, and
connect an autonomous subsystem to the SATA device, without using a
main operating system, when the system is in a second power state,
the second power state to consume less power than the first power
state.
20. (New) The apparatus of claim 19, wherein the switch connecting the SATA
device only connects to either the system or the subsystem.
21. (New) The apparatus of claim 19, wherein the switch operation is controlled by
signals from the system.